

1Metre long SCREENED “Y-CABLE-2” WIRING TABLE

25&25WAY SCREENED CABLE (WITH SCREEN WIRE&FOIL CONNECTED
TO ALL CONNECTOR SHELLS) TO BE USED

For use ONLY with: Eagle Technology PC-30Dx and PC-30F/G ISA Cards

(REVISION-1) 17/03/2000

SIGNAL NAME	PIN NUMBER DB50M * Label: PC-30DX/FG	PIN NUMBER DB25M * Label: DIGITAL	PIN NUMBER DB25M * Label: ANALOG
	PC-30DX & PC-30F/G	DIGITAL I/O MODULES	ANALOG MODULES
DAC 0	1	-	22
+12V	2	-	24
-12V	3	-	12
CH 8	4	-	5
CH 7	5	-	17
CH 5	6	-	16
CH 3	7	-	15
CH 1	8	-	14
PORT B7	9	21	-
PORT B5	10	20	-
PORT B4	11	7	-
PORT A6	12	4	-
PORT A4	13	3	-
PORT A2	14	2	-
PORT A0	15	1	-
PORT C6	16	12	-
DIG GND / +5V	17	13	-
DAC 1	18	-	10
CH 9	19	-	18
CH 0	20	-	1
EXT CLK	21	-	13
CH 6	22	-	4
CH 4	23	-	3
CH 2	24	-	2
EXT TRIG	25	-	25
PORT B6	26	8	-
PORT B3	27	19	-
PORT A7	28	17	-
PORT A5	29	16	-
PORT A3	30	15	-
PORT A1	31	14	-
PORT C7	32	25	-
PORT C5	33	24	-
DAC 3	34	-	11
DAC 2	35	-	23
CH 10	36	-	6
CH 11	37	-	19
CH 12	38	-	7
CH 13	39	-	20
CH 14	40	-	8
CH 15	41	-	21
ANALOG GND	42	-	9
PORT B0	43	5	-
PORT B1	44	18	-
PORT B2	45	6	-
PORT C3	46	23	-
PORT C2	47	10	-
PORT C1	48	22	-
PORT C0	49	9	-
PORT C4	50	11	-
DIGITAL GND	SCREEN WIRE	SCREEN WIRE	SCREEN WIRE

* Label: Means that these connector covers must be labeled:
“PC-30DX/FG”, “DIGITAL” and “ANALOG” respectively!